

<b>1. VESSEL DESCRIPTION</b>			
1.1	Date updated:	Sep 12, 2017	
1.2	Vessel's name (IMO number):	Cotopaxi (9174579)	
1.3	Vessel's previous name(s) and date(s) of change:	Not Applicable	
1.4	Date delivered / Builder (where built):	Feb 23, 1999 / Hyundai Heavy Industries Co.	
1.5	Flag / Port of Registry:	Ecuador / Guayaquil	
1.6	Call sign / MMSI:	HCCO / 735057544	
1.7	Vessel's contact details (satcom/fax/email etc.):	Tel: 00-881-677735714 / 00-881-677735842 +1401 239 0498 Fax: 373502415 Email: cot_c@internet-c.com ; cot.vsat@gmail.com	
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC):	Oil Tanker	
1.9	Type of hull:	Double Hull	
<b>Classification</b>			
1.10	Classification society:	American Bureau of Shipping	
1.11	Class notation:	ABS+ A1, Oil Carrier (E), +AMS; +ACC, VEC, SH	
1.12	Is the vessel subject to any conditions of class, class extensions, outstanding memorandums or class recommendations? If yes, give details:	No N/A	
1.13	If classification society changed, name of previous and date of change:	N/A, Not Applicable	
1.14	IMO type, if applicable:	2	
1.15	Does the vessel have ice class? If yes, state what level:	No, N/A	
1.16	Date / place of last dry-dock:	Oct 14, 2016 / TALCAHUANO, CHILE	
1.17	Date next dry dock due / next annual survey due:	Feb 28, 2019	Feb 28, 2018
1.18	Date of last special survey / next special survey due:	Oct 28, 2016	Feb 28, 2019
1.19	If ship has Condition Assessment Program (CAP), what is the latest overall rating:	Yes, 1	
1.20	Does the vessel have a statement of compliance issued under the provisions of the Condition Assessment Scheme (CAS): If yes, what is the expiry date?	N/A	
<b>Dimensions</b>			
1.21	Length overall (LOA):	228.17 Metres	
1.22	Length between perpendiculars (LBP):	220.68 Metres	
1.23	Extreme breadth (Beam):	32.20 Metres	
1.24	Moulded depth:	17.85 Metres	
1.25	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:	46.60 Metres	
1.26	Bow to center manifold (BCM) / Stern to center manifold (SCM):	115.24 Metres	112.93 Metres
1.27	Distance bridge front to center of manifold:	73.89 Metres	
1.28	Parallel body distances	Lightship	Normal Ballast
	Forward to mid-point manifold:	41.60 Metres	57.40 Metres
	Aft to mid-point manifold:	36.40 Metres	50.40 Metres
	Parallel body length:	78 Metres	107.80 Metres
1.29	FWA/TPC at summer draft:	290.00 Millimetres	67.50 Metric Tonnes
1.30	Constant (excluding fresh water):		
1.31	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?	0.61m / 02feet	
1.32	What is the max height of mast above waterline (air draft)	Full Mast	Collapsed Mast
	Lightship:	44.14 Metres	0 Metres
	Normal ballast:	39.98 Metres	0 Metres
	At loaded summer deadweight:	33.63 Metres	0 Metres
<b>Tonnages</b>			
1.33	Net Tonnage:	20,199	
1.34	Gross Tonnage / Reduced Gross Tonnage (if applicable):	35,770	
1.35	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT):	36,818	32,497
1.36	Panama Canal Net Tonnage (PCNT):	29,616	
<b>Ownership and Operation</b>			
1.37	Registered owner - Full style:	EP FLOPEC Av. DEL PACIFICO N 001 Y PUERTO RICO Edificio EP-FLOPEC	

		Sector las Palmas Esmeraldas -Ecuador Ecuador Tel: 593-6-2-999 900/ 593 Fax: 593-6-2-999974 Telex: N/A Email: g.gestionintegral@flopec.com.ec Web: www.flopec.com.ec Company IMO#: 0206335
1.38	Technical operator - Full style:	EP FLOPEC AV. DEL PACIFICO N 001 Y PUERTO RICO EDIFICIO EP-FLOPEC SECTOR LAS PALMAS ESMERALDAS-ECUADOR Ecuador Tel: 593-6-2-999 900 ext Fax: 593-6.-2999974 Telex: Not Applicable Email: operaciones@flopec.com.ec Web: www.flopec.com.ec Company IMO#: 0206335
1.39	Commercial operator - Full style:	Panamax International c/o Cape Tankers Inc. Tower Financial Center, 16th Floor, 50th Street and Elvira Mendez P.O BOX 0816-01560, Panama City, Panama Panama Tel: +1 954 771 7757 Telex: Not Applicable Email: cape@capetankers.com
1.40	Disponent owner - Full style:	Panamax International Trust Company Complex, Ajeltake Road, Ajeltake Island, Majuro, Marshall Islands MH96960 Tel: +1 954 771 7757 Telex: N/A Email: cape@capetankers.com Web: www.panamaxinternational.com

2.	CERTIFICATION	Issued	Last Annual	Expires
2.1	Safety Equipment Certificate (SEC):	Jan 30, 2014	May 08, 2017	Feb 27, 2019
2.2	Safety Radio Certificate (SRC):	Jan 30, 2014	May 08, 2017	Feb 27, 2019
2.3	Safety Construction Certificate (SCC):	Jan 30, 2014	May 08, 2017	Feb 27, 2019
2.4	International Loadline Certificate (ILC):	Jan 30, 2014	May 17, 2017	Feb 27, 2019
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Jan 30, 2014	May 15, 2017	Feb 27, 2019
2.6	ISM Safety Management Certificate (SMC):	Feb 13, 2015	Jun 03, 2015	Feb 28, 2018
2.7	Document of Compliance (DOC):	Oct 14, 2015	Apr 21, 2017	Apr 26, 2018
2.8	USCG Certificate of Compliance (COC):	Oct 03, 2012	Oct 03, 2012	Oct 03, 2014
2.9	Civil Liability Convention (CLC) 1992 Certificate:	Feb 20, 2017	Not Applicable	Feb 20, 2018
2.10	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Feb 20, 2017	Not Applicable	Feb 20, 2018
2.11	Ship Sanitation Control (SSCC)/Ship Sanitation Control Exemption (SSCE) Certificate:	Jul 22, 2017	Not Applicable	Jan 22, 2018
2.12	U.S. Certificate of Financial Responsibility (COFR):	Jul 31, 2015	Not Applicable	Jul 31, 2018
2.13	Certificate of Class (COC):	Mar 16, 2014	May 17, 2017	Feb 28, 2019
2.14	International Sewage Pollution Prevention Certificate (ISPPC):	Jan 30, 2014	Not Applicable	Feb 27, 2019
2.15	Certificate of Fitness (COF):			
2.16	International Energy Efficiency Certificate (IEEC):	Mar 16, 2014	Not Applicable	Not Applicable
2.17	International Ship Security Certificate (ISSC):	Jun 06, 2014	None	May 27, 2019
2.18	International Air Pollution Prevention Certificate (IAPPC):	Mar 16, 2014	May 17, 2017	Feb 28, 2019
2.19	Maritime Labour Certificate (MLC):	Aug 05, 2014	Not Applicable	Aug 04, 2019
<b>Documentation</b>				
2.20	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:		Yes	
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?		Yes	
2.22	Is the ITF Special Agreement on board (if applicable)?			
2.23	ITF Blue Card expiry date:			

<b>3.</b>	<b>CREW</b>	
3.1	Nationality of Master:	Ecuadorean
3.2	Number and Nationality of Officers:	10 Ecuadorean
3.3	Number and Nationality of Crew:	16 ALL ECUADORIAN
3.4	What is the common working language onboard:	SPANISH
3.5	Do officers speak and understand English?	Yes
3.6	If Officers/Crew employed by a Manning Agency - Full style:	<p>Officers:  EP FLOTA PETROLERA ECUATORIANA  Av.DEL PACIFICO N 001 Y PUERTO RICO  ESMERALDAS ECUADOR  Tel: 593-4-2-302999 / 593  Fax: 593-4-2-560-404  Telex: Not Applicable  Email: personal.emb@flopec.com.ec  Web: www.flopec.com.ec</p> <p>Crew:  EP FLOTA PETROLERA ECUATORIANA  Av.DEL PACIFICO N 001 Y PUERTO RICO  ESMERALDAS ECUADOR  Tel: 593-4-2-302999 / 593  Fax: 593-4-2-560-404  Telex: Not Applicable  Email: personal.emb@flopec.com.ec  Web: www.flopec.com.ec</p>

<b>4.</b>	<b>FOR USA CALLS</b>	
4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter?	Yes
4.2	Qualified individual (QI) - Full style:	Gallagher Marine System, Inc. 100 Century Parkway, suite 130 Mt. Laurel, NJ 08054 United States Tel: 1-703-683-4700 Fax: 1856-642-3945 Telex: N/A Email: inf@chgms.com
4.3	Oil Spill Response Organization (OSRO) - Full style:	National Response Corp. 3500 Sunrise Highway, suite T103 Great River, NY 11739 Tel: 1-631-224-9141 Fax: 1-631-224-9082 Telex: N/A Email: iocdo@nrcc.com

<b>5.</b>	<b>CARGO AND BALLAST HANDLING</b>				
<b>Double Hull Vessels</b>					
5.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:				Yes, Solid
<b>Loadline Information</b>					
5.2	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	4.88 Metres	12.97 Metres	66,160 Metric Tonnes	78,336 Metric Tonnes
	Winter:	5.15 Metres	12.70 Metres	64,340 Metric Tonnes	76,516 Metric Tonnes
	Tropical:	4.61 Metres	13.24 Metres	67,985 Metric Tonnes	80,161 Metric Tonnes
	Lightship:	15.35 Metres	2.50 Metres	Not Applicable	12,176 Metric Tonnes
	Normal Ballast Condition:	11.23 Metres	6.62 Metres	25,547 Metric Tonnes	37,723 Metric Tonnes
5.3	Does vessel have multiple SDWT? If yes, please provide all assigned loadlines:				No
<b>Cargo Tank Capacities</b>					
5.4	Number of cargo tanks and total cubic capacity (98%):			12 + 2 slops	69,014 Cu. Metres
5.5	Capacity (98%) of each natural segregation with double valve (specify tanks):			1-3-5-Slop (P&S) = 35384.6 Cu. Metres	

		2-4-6 (P&S) = 35385.0 Cu. Metres Total = 707769.60 CM 98%			
5.6	Number of slop tanks and total cubic capacity (98%):		1,755.60 Cu. Metres		
5.7	Specify segregations which slops tanks belong to and their capacity with double valve:	1-3-5-Slop (P&S) = 35385.0 Cu. Metres			
5.8	Residual/Retention oil tank(s) capacity (98%), if applicable:	27.20 Cu. Metres			
5.9	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):	SBT			
<b>SBT Vessels</b>					
5.10	What is total SBT capacity and percentage of SDWT vessel can maintain?	26,137.10 Cu. Metres	40.00 %		
5.11	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:	Yes			
<b>Cargo Handling and Pumping Systems</b>					
5.12	How many grades/products can vessel load/discharge with double valve segregation:	2			
5.13	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:	No			
5.14	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Cargo Pumps:	2	Centrifugal	3000 M3/HR	110 Metres 110 Metres
	Cargo Eductors:	1	TEAMTEC-GOLAR STRIPPING EJECTOR type 6-8-10 d57	300 Cu. Metres/Hour	25 Metres
	Stripping:	1	Reciprocating	200 Cu. Metres/Hour	110 Metres
	Ballast Pumps:	2	Centrifugal	1,200 Cu. Metres/Hour	25 Metres
	Ballast Eductors:	1	ELLEHAMMER EJECTOR type 125-150-200/95-49,5	150 Cu. Metres/Hour	5 Metres
5.15	Max loading rate for homogenous cargo per manifold connection:	4,000 Cu. Metres/Hour			
5.16	Max loading rate for homogenous cargo loaded simultaneously through all manifolds:	8,000.00 Cu. Metres/Hour			
5.17	How many cargo pumps can be run simultaneously at full capacity:	2			
<b>Cargo Control Room</b>					
5.18	Is ship fitted with a Cargo Control Room (CCR)?	Yes			
5.19	Can tank innage / ullage be read from the CCR?	Yes			
<b>Gauging and Sampling</b>					
5.20	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6?	Yes			
5.21	What type of fixed closed tank gauging system is fitted:	Radar			
5.22	Number of portable gauging units (example- MMC) on board:	6			
5.23	Are overfill (high) alarms fitted? If Yes, indicate whether to all tanks or partial:	Yes, All			
5.24	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:	Yes,			
5.25	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:	Yes,			
<b>Vapor Emission Control System (VECS)</b>					
5.26	Is a Vapour Emission Control System (VECS) fitted?	Yes			
5.27	Number/size of VECS manifolds (per side):	2	400 Millimetres		
5.28	Number / size / type of VECS reducers:	2 x 400 mm			
<b>Venting</b>					
5.29	State what type of venting system is fitted:	common line mast raise + individual high velocity PV VALVES			
<b>Cargo Manifolds and Reducers</b>					
5.30	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?	Yes			
5.31	Total number / size of cargo manifold connections on each side:	2 / 400.00 Millimetres			
5.32	What type of valves are fitted at manifold:	Butterfly/MANUAL			
5.33	What is the material/rating of the manifold:	STEEL / ASA			
5.34	Does the vessel have a Common Line Manifold connection? If yes, describe:				
5.35	Distance between cargo manifold centers:	2,500.00 Millimetres			
5.36	Distance ships rail to manifold:	4,400.00 Millimetres			
5.37	Distance manifold to ships side:	4,600.00 Millimetres			
5.38	Top of rail to center of manifold:	60.00 Millimetres			

5.39	Distance main deck to center of manifold:	2,000.00 Millimetres	
5.40	Spill tank grating to center of manifold:	900.00 Millimetres	
5.41	Manifold height above the waterline in normal ballast / at SDWT condition:	13.30 Metres	6.99 Metres
5.42	Number / size / type of reducers:	4 x 500/400mm (20/16") 2 x 500/300mm (20/12") 2 x 500/250mm (20/10") 2 x 500/200mm (20/8") 2 x 400/250mm (16/10") JIS	
5.43	Is vessel fitted with a stern manifold? If yes, state size:	No,	

#### Heating

5.44	Cargo / slop tanks fitted with a cargo heating system?	Type	Coiled	Material
	Cargo Tanks:	Heating coils	Yes	Other
	Slop Tanks:			
5.45	Maximum temperature cargo can be loaded / maintained:	72.0 °C / 161.6 °F	60 °C / 140 °F	
5.46	Minimum temperature cargo can be loaded / maintained:			

#### Coating / Anodes

5.47	Tank Coating	Coated	Type	To What Extent	Anodes
	Cargo tanks:	Yes	HIGH BUILD POLYAMIDE CURED COAL TAR EPOXY/POLYAMIDE CURED EPOXY HOLDING PRIMER	VAPOUR SPACE AND BOTTOM	No
	Ballast tanks:	Yes	Epoxy Resin Based Tar Free	Other	Yes
	Slop tanks:	Yes	HIGH BUILD POLYAMIDE CURED COAL TAR EPOXY/POLYAMIDE	Whole Tank	

#### 6. INERT GAS AND CRUDE OIL WASHING

6.1	Is a Crude Oil Washing (COW) installation fitted / operational?	Yes / Yes
6.2	Is an Inert Gas System (IGS) fitted / operational?	Yes / Yes
6.3	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	Flue Gas

#### 7. MOORING

7.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	0	0 Millimetres		0 Metres	0 Metric Tonnes
	Main deck fwd:	0	0 Millimetres		0 Metres	0 Metric Tonnes
	Main deck aft:	0	0 Millimetres		0 Metres	0 Metric Tonnes
	Poop deck:	0	0 Millimetres		0 Metres	0 Metric Tonnes
7.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	64.00 Millimetres	NYLON MULTIFILAMENT	11.00 Metres	64.80 Metric Tonnes
	Main deck fwd:	2	64.00 Millimetres	NYLON MULTIFILAMENT	11.00 Metres	64.80 Metric Tonnes
	Main deck aft:	2	64.00 Millimetres	NYLON MULTIFILAMENT	11.00 Metres	64.80 Metric Tonnes
	Poop deck:	4	64.00 Millimetres	NYLON MULTIFILAMENT	11.00 Metres	64.80 Metric Tonnes
7.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	30.00 Millimetres	DYNEEMA	220.00 Metres	71.50 Metric Tonnes
	Main deck fwd:	2	30.00 Millimetres	DYNEEMA	220.00 Metres	71.50 Metric Tonnes
	Main deck aft:	2	30.00 Millimetres	DYNEEMA	220.00 Metres	71.50 Metric Tonnes
	Poop deck:	4	30.00 Millimetres	DYNEEMA	220.00 Metres	71.50 Metric Tonnes
7.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	10	28 Millimetres	DYNEEMA	220 Metres	70 Metric Tonnes
	Main deck fwd:					
	Main deck aft:					
	Poop deck:	17	56 Millimetres	POLYESTER-POLYSTEEL	220 Metres	64 Metric Tonnes
7.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	2	Double Drums	Hydraulic	42.90 Metric Tonnes	
	Main deck fwd:	2	Single Drum	Hydraulic	42.90 Metric Tonnes	

	Main deck aft:	2	Single Drum	Hydraulic	42.90 Metric Tonnes	
	Poop deck:	2	Double Drums	Hydraulic	42.90 Metric Tonnes	
7.6	Bitts, closed chocks/fairleads		No. Bitts	SWL Bitts	No. Closed Chocks	SWL Closed Chocks
	Forecastle:	4		52 Metric Tonnes	9	51 Metric Tonnes
	Main deck fwd:	5		52 Metric Tonnes	16	51 Metric Tonnes
	Main deck aft:	5		52 Metric Tonnes	11	51 Metric Tonnes
	Poop deck:	6		52 Metric Tonnes	14	51 Metric Tonnes

#### Anchors/Emergency Towing System

7.7	Number of shackles on port / starboard cable:				12 / 12	
7.8	Type / SWL of Emergency Towing system forward:			TONGUE CHAIN STOPPER		200 Metric Tonnes
7.9	Type / SWL of Emergency Towing system aft:			WIRE ETS 200-D		200 Metric Tonnes

#### Escort Tug

7.10	What is size / SWL of closed chock and/or fairleads of enclosed type on stern:				520	92.00 Metric Tonnes
7.11	What is SWL of bollard on poop deck suitable for escort tug:					92.00 Metric Tonnes

#### Bow/Stern Thruster

7.12	What is brake horse power of bow thruster (if fitted):			No,		
7.13	What is brake horse power of stern thruster (if fitted):			No,		

#### Single Point Mooring (SPM) Equipment

7.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)'?					Yes
7.15	If fitted, how many chain stoppers:				1	
7.16	State type / SWL of chain stopper(s):			TONGUE		200.00 Metric Tonnes
7.17	What is the maximum size chain diameter the bow stopper(s) can handle:					78.00 Millimetres
7.18	Distance between the bow fairlead and chain stopper/bracket:					2,670 Millimetres
7.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:			Yes		

#### Lifting Equipment

7.20	Derrick / Crane description (Number, SWL and location):				Cranes: 1 x 15.00 Tonnes center	
7.21	What is maximum outreach of cranes / derricks outboard of the ship's side:					3.90 Metres

#### Ship To Ship Transfer (STS) / Helicopter Operations

7.22	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquefied Gas, as applicable)?					Yes
7.23	Can the ship comply with the ICS Helicopter Guidelines? If Yes, state whether winching or landing area provided and diameter of the circle provided:			Yes, Winching		5.00 Metres

### 8. MISCELLANEOUS

#### Engine

8.1	Speed			Maximum		Economic
	Ballast speed:			14.50 Knots (WSNP)		12.50 Knots (WSNP)
	Laden speed:			14.50 Knots (WSNP)		12.50 Knots (WSNP)
8.2	What type of fuel is used for main propulsion / generating plant:			IFO 380		IFO 380
8.3	Type / Capacity of bunker tanks:			Fuel Oil: 1,872 Cu. Metres Diesel Oil: 131 Cu. Metres Gas Oil: 1.30 Cu. Metres		
8.4	Is vessel fitted with fixed or controllable pitch propeller(s):			Fixed		
8.5	Engines	No		Capacity		Make/Type
	Main engine:	1		8,080 Kilowatt		Hyundai - Man B&W 5S60 MC
	Aux engine:	3		600 Kilowatt		Huyndai - Man B&W L 23/30
	Power packs:					
	Boilers:	2		20.00 Metric Tonnes/Hour		AALBORG SUNROD CPH 20 T/H

#### Emissions

8.6	Main engine IMO NOx emission standard:					
-----	--	--	--	--	--	--

8.7	Energy Efficiency Design Index (EEDI) rating number:	
<b>Insurance</b>		
8.8	P & I Club - Full Style:	WEST OF ENGLAND TOWER BRIDGE COURT 226 TOWER BRIDGE ROAD LONDON SE1 2UP Tel: +(352) 4700671 Fax: +(352) 225253 Email: mail@westpandi.com Web: www.westpandi.com
8.9	P & I Club pollution liability coverage / expiration date:	1,000,000,000 US\$ Feb 20, 2018
8.10	Hull & Machinery insured by - Full Style:	
8.11	Hull & Machinery insured value / expiration date:	45,000,000 US\$
<b>Recent Operational History</b>		
8.12	Date and place of last Port State Control inspection:	Aug 23, 2016 / Callao
8.13	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No
8.14	Has vessel been involved in a pollution, grounding, serious casualty or collision incident during the past 12 months? If yes, full description:	Pollution: No, Grounding: No, Casualty: No, Collision: No,
8.15	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	FUEL OIL 6 ESMERALDAS SAN JOSE ACAJUTLA  FUEL OIL 4 PETROECUADOR ESMERALDAS  FUEL OIL 4 PETROECUADOR STS LA LIBERTAD
8.16	Date/place of last STS operation:	Jun/25/2017 Esmeraldas - Ecuador
<b>Vetting</b>		
8.17	Date of last SIRE inspection:	Sep 06, 2017
8.18	Date of last CDI inspection:	
8.19	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: <i>* "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.</i>	SHELL, REPSOL, AND PHILLIPS
<b>Additional Information</b>		
8.20	Additional information relating to features of the ship or operational characteristics:	

Rev 2015 ([INTERTANKO](http://www.intertanko.com) / [Q88.com](http://www.q88.com))

Form completed on <http://www.q88.com/integration.aspx> Please email [support@q88.com](mailto:support@q88.com) an updated copy if this is not the latest version.